

# EGIL200

## Circuit breaker analyser

# Megger<sup>®</sup>



- Mid-range circuit breaker analyser providing a new level of accuracy to your standard measurements
- Intuitive operation offers final measurement results with a minimum of user interaction
- Measurement performance inherited from market leader Megger TM series circuit breaker analysers
- Instrument and accessories designed for the most demanding field conditions
- Easy-to-use and intuitive interface

### DESCRIPTION

EGIL200 is the first incarnation in a new range of circuit breaker analysers from Megger. It has been designed in close cooperation with global industry reference groups drawing experience from the market leading and hugely successful Megger TM series of circuit breaker analysers.

The emphasis in the development of the EGIL200 has been on ease of use, ensuring that the time spent on setting up measurements is kept to a minimum. As such, with the EGIL200, you can get your test results done in no time.

Connection to the test object has also been streamlined and with only one hook-up, all following operations or measurements can be made:

1. Timing of main and PIR contacts
2. Coil current analysis of close, open 1 and 2 coils
3. Station voltage measurements
4. Motion measurements
5. Motor current measurement
6. Minimum pickup voltage test for close, open 1 and open 2

The patented DualGround™ timing using the DCM module makes the testing safe and time saving by keeping the circuit breaker grounded on both sides throughout the test. The DCM module uses a measuring technology called Dynamic Capacitive Measurement.

With both main instrument and accessories designed for the most demanding field conditions, EGIL200 is your complete toolbox for daily, hassle-free circuit breaker condition assessments.

### BENEFITS


EGIL200 offers all standard measurements from IEEE C37 and IEC 62271 standards and brings high-end features from the TM series into the affordable mid-range segment:

- Offers all standard measurements based on international standards
- Intuitive and user-friendly operation – a minimum of user interventions needed from power-up of instrument to documented measurement result
- Instrument fitted in rugged IP67 rated case and accessories in easy-to-carry backpack
- Designed for medium to high voltage circuit breakers
- One-click reporting to pdf or printed on optional, integrated printer
- Dedicated control output for open coil 2
- Multi-functional control channels that, with only one connection, manage control pulses and can measure station voltages and coil currents
- Galvanically insulated and polarity independent auxiliary contact timing channels, automatically adapted for dry and wet contacts
- Accurate pre-insertion resistor contact timing and resistance value measurement thanks to patented Active Interference Suppression technology
- Static and dynamic resistance measurement on up to three contacts simultaneously (model depending).

## EGIL200 Circuit breaker analyser

### FEATURES AND BENEFITS

- 1. CONTROL**  
Breaker control (close, open 1 and open 2) and external trig inputs  
Station voltage and coil current measurement
- 2. PARKING SPACE**  
For safe disconnection of coil circuits
- 3. TIMING AUX**  
3 channels for auxiliary contact timing and external trig
- 4. DIGITAL**  
3 digital inputs for incremental motion transducers
- 5. 1-3 BNC INPUTS**  
1-3 BNC inputs dedicated for current clamps
- 6. MULTI-PURPOSE CHANNELS**  
1-3 multi-purpose analog channels
- 7. TIMING M/R, DRM/VDS**  
Timing of main and resistor contacts, DRM, SRM and CT / VDS-timing on 1 break per phase (Only EGIL211, EGIL213)
- 8. TIMING M/R**  
Timing of main and resistor contacts on up to 4 breaks per phase (Only EGIL221, EGIL223, EGIL241, EGIL243)
- 9. DCM DualGround™**  
Input for 1-2 DCM200 (opt. accessory), for main contact timing with both sides grounded
- 10. DRM**  
DRM control output (opt. accessory)
- 11. USB AND ETHERNET PORT**  
3 × USB A, 1 × USB B and 1 × RJ45
- 12. LCD SCREEN**  
7" high visibility touch screen
- 13. OPERATE / MEASURE ROTARY SWITCH**
- 14. ICONOGRAPHY**  
Contrast rich iconography for best visibility and understanding
- 15. USER INTERFACE**  
Workflow based (Nameplate, test settings, connections, results, report)
- 16. PRINTER**  
Optional 4" thermal printer
- 17. COLOUR CODED CONNECTORS AND LEADS**  
For easy verification of connections



## EGIL200 Circuit breaker analyser

### SPECIFICATIONS EGIL200

Specifications are valid after 30 minutes warm up time.  
System time base drift 0.001 % per year.  
Specifications are subject to change without notice.

#### Environment

**Application field** For use in medium and high voltage substations and industrial environments

#### Temperature

Operating -20 °C to +55 °C (-4 °F to +131 °F)

Storage & transport -30 °C to +70 °C (-40 °F to +158 °F)

#### Humidity

5 % – 95 % RH, non-condensing

#### Altitude

Operating Up to 2000 m (6562 ft) max. 240 V AC / 250 V DC on mains, max. 250 V AC / 300 V DC on CONTROL and TIMING AUX inputs.  
Between 2000 m (6562 ft) and 5000 m (16404 ft) max. 150 V AC / DC on mains, CONTROL and TIMING AUX inputs

#### CE-marking

LVD 2014/35/EU

EMC 2014/30/EU

RoHS 2011/65/EU

#### General

Mains input (nominal) 100 – 240 V AC, 50 / 60 Hz, 120 – 250 V DC

Power consumption 200 VA (max.)

Dimensions 474 x 415 x 214 mm (18.7" 16.3" 8.4")

Weight 12 kg (26.5 lbs)

IP-rating (IEC 60529):

Closed case IP67

Open case IP20

Data memory capacity 1.4 GB, corresponding to up to 6000 basic recordings or up to 1500 advanced recordings

#### Display

7" (17.8 cm) LCD, Capacitive touch screen

Available languages English, French, German, Spanish, Swedish, Polish and Chinese

#### Communication interfaces



3 USB A, 1 USB B for connection to external PC



RJ45 for connection to external PC

Keyboard On-screen and optional USB keyboard

#### External outputs

##### Trig output for SDRM20X

Output voltage 12 V DC  $\pm 10$  %

Short circuit protection PTC 250 mA

Switching current <250 mA, resistive load

#### Control section

##### General

Control pulse outputs Close, open 1 and open 2 (Galvanically insulated from earth and each other)

Time base inaccuracy  $\pm 0.01$  % of reading  $\pm 1$  sample interval

Max. sample rate 40 kHz

Measurement time Up to 10 s

#### Non-bouncing switch

Max. current 60 A AC / DC, pulse  $\leq 20$  ms

Max. continuous current 5 A

Duration User configurable in steps of 1 ms

Delay User configurable in steps of 1 ms

<sup>1</sup>With standard 5 m test leads and floating test object

#### Current measurement

Measurement range  $\pm 80$  A

Resolution 16 bits

Inaccuracy  $\pm 2$  % of reading  $\pm 0.1$  % of range

#### Voltage measurement

Max. voltage 250 V AC,  $\pm 300$  V DC

Measurement range  $\pm 400$  V

Resolution 16 bit

Inaccuracy  $\pm 1$  % of reading  $\pm 0.1$  % of range

#### Timing M/R section

##### General

No. of channels 3, 6 or 12 selectable at ordering

Time base inaccuracy  $\pm 0.01$  % of reading  $\pm 1$  sample interval

Min. detected contact bounce 0.05 ms

Max. sample rate 40 kHz

Measurement time Up to 10 s

##### Timing of main and resistor contacts

Open circuit voltage Toggling  $\pm 12$  V  $\pm 10$  %

Short circuit current 22 mA  $\pm 10$  %

##### 50/60 Hz interference suppression

Active Interference Suppression, Megger patent

##### Transient disturbance suppression

Smart digital filter

##### Status threshold

User configurable thresholds

Main Closed < 10  $\Omega$  < Open (Factory default)

Main and resistor Main < 10  $\Omega$  < PIR < 2 k $\Omega$  < Open (Factory default)

##### PIR resistance measurement

Supported PIR types Linear PIR

Measurement range 10  $\Omega$  – 10 k $\Omega$

Inaccuracy  $\pm 5$  % of reading  $\pm 0.1$  % of range<sup>1</sup>

##### Voltage measurement (Only TIMING M/R, DRM/VDS inputs)

Measurement ranges  $\pm 50$  V and  $\pm 2.5$  V

Resolution 16 bits

Inaccuracy  $\pm 1$  % of reading  $\pm 0.1$  % of range

## EGIL200

### Circuit breaker analyser

#### Analog section

##### General

No. of channels	1 or 3 isolated channels
Time base inaccuracy	$\pm 0.01$ % of reading $\pm 1$ sample interval
Max. sample rate	40 kHz
Measurement time	Up to 10 s
Transducer resistance	500 $\Omega$ – 5 k $\Omega$

##### Output

Voltage	10 V DC $\pm 5$ %
Max. output current	30 mA

##### Voltage measurement

Max. voltage	$\pm 10 V_{\text{peak}}$
Measurement ranges	$\pm 1$ V and $\pm 10$ V
Resolution	16 bits

##### Inaccuracy

1 V range	$\pm 0.1$ % of reading $\pm 0.1$ % of range
10 V range	$\pm 1$ % of reading $\pm 0.1$ % of range

##### External current measurement

Max. input	$\pm 1 V_{\text{peak}}$
Scaling	Selectable in software

#### Digital section

##### General

No. of channels	3
Supported types	Incremental transducers, RS422
Time base inaccuracy	$\pm 0.01$ % of reading $\pm 1$ sample interval
Max. sample rate	40 kHz
Measurement time	Up to 10 s

##### Output

Voltage	12 V DC $\pm 5$ %
Max. output current	300 mA

##### Digital input

Range	$\pm 32000$ pulses
Resolution	1 pulse
Inaccuracy	$\pm 1$ pulse

#### Timing Aux section

##### General

No. of channels	3 isolated channels
Time base inaccuracy	$\pm 0.01$ % of reading $\pm 1$ sample interval
Max. sample rate	40 kHz
Measurement time	Up to 10 s
Max. voltage	250 V AC, $\pm 300$ V DC

##### Contact mode

Open circuit voltage	24 V DC $\pm 5$ %
Short circuit current	10 mA DC $\pm 5$ %
User configurable status threshold	Open < -10 V < Closed < 10 V < Open (Factory default)

##### Printer (optional)

Type	Thermal printer
Paper width	112 mm, 114 mm (4.41", 4.48")
Operating temperature	0 °C to +60 °C (32 °F to +140 °F)
Storage & transport	-20 °C to +70 °C (-4 °F to +158 °F)

## EGIL200

### Circuit breaker analyser






#### Included cables

Each model is delivered with the necessary number of timing cables to fit the amount of timing channels available

		2 and 4 breaks per phase	1 break per phase	
		High voltage lead kit	Medium voltage lead kit	High voltage lead kit
<b>GA-00850</b> 	<b>Timing M/R cable</b> For 2 breaks/phase <ul style="list-style-type: none"> <li>XLR3 male to banana connector, 5 m (16.4 ft)</li> <li>Length of the split portion (retractable sock), 2.4 m (8 ft) to 3.8 m (12 ft)</li> </ul>	✓		
<b>GA-00851</b> 	<b>Timing M/R extension cable</b> <ul style="list-style-type: none"> <li>XLR3 male to XLR3 female, 10 m (32.8 ft)</li> </ul>	✓		✓
<b>GA-00853</b> 	<b>Timing M/R medium voltage cable</b> <ul style="list-style-type: none"> <li>3 x XLR3 male to banana, 3 m (9.8 ft)</li> <li>Length of the split portion 0.5 m (1.6 ft)</li> </ul>		✓	
<b>GA-00854</b> 	<b>Timing M/R high voltage cable</b> For 1 break/phase <ul style="list-style-type: none"> <li>XLR3 male to banana, 5 m (16.4 ft)</li> <li>Length of the split portion (retractable sock), 2.4 m (8 ft) to 3.8 m (12.5 ft)</li> </ul>			✓
<b>GA-00871</b> 	<b>Timing AUX cable</b> <ul style="list-style-type: none"> <li>6 banana test leads in a common sleeve, 5 m (16.4 ft)</li> <li>Length of the split portion, 0.5 m (1.6 ft)</li> <li>Includes connection adapters</li> </ul>	✓	✓	✓
<b>GA-90002</b> 	<b>Control cable kit</b> <ul style="list-style-type: none"> <li>5 banana test leads in a common sleeve, 5 m (16.4 ft)</li> <li>Length of the split portion (retractable sock), 0.5 m (1.6 ft) to 1.5 m (4.9 ft).</li> <li>Includes connection adapters</li> </ul>	✓	✓	✓

## EGIL200 Circuit breaker analyser

### Included accessories

		2 and 4 breaks per phase	1 break per phase	
		High voltage lead kit	Medium voltage lead kit	High voltage lead kit
<b>KD-03040</b> 	<b>Timing M/R clamp</b> <ul style="list-style-type: none"> <li>Banana connector and strain relief</li> </ul>	✓	✓	✓
<b>GA-01005</b> 	<b>Analog cable</b> <ul style="list-style-type: none"> <li>Screened cable</li> <li>XLR3 female to XLR3 male, 10 m (32,8 ft)</li> </ul>	✓	✓	✓
<b>CM-8200X</b> 	<b>EGIL200 Viewer Basic</b> <ul style="list-style-type: none"> <li>The PC software EGIL200 Viewer is used to analyze results and create pdf reports</li> <li>The installation file is preloaded on the supplied USB memory</li> </ul>	✓	✓	✓
<b>2012-180</b> 	<b>Lead and accessory bag</b> <ul style="list-style-type: none"> <li>Lead and accessory bag with backpack straps and hand straps.</li> <li>Variable height through zipper solution.</li> <li>Dimensions 580x355x165/228 mm (23" x 14" x 6.5"/9")</li> </ul>	✓	✓	✓
<b>GC-00100</b> 	<b>Thermal printing paper</b> <ul style="list-style-type: none"> <li>Only for models with printer</li> </ul>			
<b>Other material included in delivering</b> <ul style="list-style-type: none"> <li>Protective earth (PE) cable 5 m (16.4 ft)</li> <li>Ethernet cable 5 m (16.4 ft)</li> <li>USB cable 3 m (9.8 ft)</li> <li>USB memory stick</li> <li>Lead ties</li> <li>Power cable</li> <li>User Guide</li> </ul>		✓	✓	✓

## EGIL200 Circuit breaker analyser

### Optional accessories

<p><b>XB-51020</b></p> 	<p><b>Universal transducer mounting kit</b></p> <ul style="list-style-type: none"> <li>■ Fits linear and rotary travel transducers</li> </ul>	<p><b>GA-00874</b></p> 	<p><b>SDRM voltage sense adapter</b></p> <ul style="list-style-type: none"> <li>■ SDRM voltage sense adapter for EGIL200 Analog input.</li> <li>■ XLR3 female / XLR3 male, 0.3 m (1 ft)</li> <li>■ For EGIL223 and EGIL243</li> </ul>
<p><b>XB-39131</b></p> 	<p><b>Rotary digital transducer kit</b></p> <ul style="list-style-type: none"> <li>■ With 10 m (33 ft) cable and flexible coupling</li> <li>■ Fits with transducer mounting kit XB-51020</li> </ul>	<p><b>CG-90260/CG-90263</b></p> 	<p><b>SDRM201</b></p> <ul style="list-style-type: none"> <li>■ SRM/DRM on one contact at a time (CG-90260)</li> <li>■ Three-phase SRM/DRM on breakers with 1 break/phase (CG-90263)</li> <li>■ Requires software license CM-8003X</li> </ul>
<p><b>GA-00891</b></p> 	<p>■ Fits with transducer mounting kit XB-51020</p> <ul style="list-style-type: none"> <li>■ neutriCON female to neutriCON male, 10 m (33 ft)</li> </ul>	<p><b>BL-90700/BL-90710</b></p> 	<p><b>First trip kits</b></p> <ul style="list-style-type: none"> <li>■ For analysis of first trip behaviour</li> <li>■ For single operating mechanism, 1 + 3 clamps (BL-90700)</li> <li>■ For three operating mechanisms, 3 + 3 clamp (BL-90710)</li> </ul>
<p><b>GA-00886</b></p> 	<p><b>Cable adapter</b></p> <ul style="list-style-type: none"> <li>■ EGIL200 digital to TM17/1800 transducers</li> <li>■ neutriCON male to DSUB15 female, 0.3 m (1 ft)</li> </ul>	<p><b>GA-00873</b></p> 	<p><b>Current clamp adapter</b></p> <ul style="list-style-type: none"> <li>■ EGIL200 Timing M/R, DRM/VDS input</li> <li>■ XLR3 male / BNC female, 0.3 m (1 ft)</li> </ul>
<p><b>XB-30017</b></p> 	<p><b>Linear analog transducer TLH-225</b></p> <ul style="list-style-type: none"> <li>■ 225 mm (8.8") travel</li> <li>■ Fits with transducer mounting kit XB-51020</li> </ul>	<p><b>XA-11620</b></p> 	<p><b>Current clamp</b></p> <ul style="list-style-type: none"> <li>■ With BNC connector</li> <li>■ Ranges: 30/300 A DC/AC, 10/1 mV / A</li> <li>■ Cable length 2 m (6.6 ft)</li> </ul>
<p><b>CM-09290/ CM-09292</b></p>  <p>Safe testing with both sides grounded.</p> 	<p><b>DCM200 DualGround™ timing</b></p> <ul style="list-style-type: none"> <li>■ CM-09290 (DCM200 + 3 test cables and 6 clamps)</li> <li>■ CM-09292 (DCM200 + 6 test cables and 12 clamps)</li> <li>■ Test cables, 11 m (35 ft)</li> <li>■ Requires software license CM-8002X</li> </ul>	<p><b>GD-31070</b></p> 	<p><b>Soft Carrying transport case</b></p> <ul style="list-style-type: none"> <li>■ Fits EGIL200 and one lead bag</li> <li>■ Dimensions: 66 x 46 x 46 cm (26" x 18" x 18")</li> </ul>
<p><b>GA-00857</b></p>	<ul style="list-style-type: none"> <li>■ DCM200 extension cable, neutriCON female / neutriCON male, 5 m (16.4 ft). To extend the cable between EGIL200 and DCM200.</li> </ul>	<p><b>GD-31055</b></p> 	<p><b>Soft cable case</b></p> <ul style="list-style-type: none"> <li>■ With 11 compartments, shoulder strap and two handles</li> <li>■ Made from sturdy nylon fabric.</li> <li>■ Dimensions: 74 x 27 x 42 cm (29" x 11" x 17")</li> </ul> <p><b>Note: No cables included</b></p>

## EGIL200 Circuit breaker analyser

### RECOMMENDED CONFIGURATIONS


Circuit breaker type	Medium voltage	High voltage, 1 break/phase	High voltage, 2 breaks/phase	High voltage, 4 breaks/phase	High voltage, 4 breaks/phase
Product name	EGIL211	EGIL213	EGIL223	EGIL241	EGIL243
Application	Configured for basic tests of medium voltage circuit breakers. Compatible with the option VDS timing.	Tests gang and independent pole operated medium and high voltage circuit breakers of live and dead tank type. Compatible with the options VDS timing and three-phase DRM.	Base model which performs all standard tests of modern high voltage circuit breakers	Standard tests for circuit breakers with more than two breaks per phase, including integrated thermal printer.	Max configuration for circuit breakers with more than two breaks per phase, including integrated thermal printer.
Break per phase	1	1	2	4	4
Analog input	1	3	3	1	3
Printer option	✓			✓	✓
Part number	CM-21191	CM-21380	CM-22390	CM-24191	CM-24391

Note! Only Circuit breaker standard software package is included in these configurations. Additional software packages or features need to be ordered separately, see section "Software" below.

### CUSTOM CONFIGURATIONS

EGIL200 can be ordered either in preconfigured, standard configurations including main unit and accessories or in fully customizable configurations.

#### EGIL200 naming and part number structure



## EGIL200

### Circuit breaker analyser

#### EGIL200 SOFTWARE PACKAGES AND FEATURES

Select your own EGIL Software.		Software packages		Single feature add-ons				
		Standard	Plus	Online	DualGround	SDRM	Under-voltage release	Pass / Fail
Standard software package (CM-8010X) included in all EGIL200 versions.								
<b>Types</b>								
<b>Timing</b>	Conventional	✓	✓					
	Dual-Ground™		✓		✓			
	VDS		✓	✓				
<b>Contact resistance</b>	Manual	✓	✓					
	SDRM		✓			✓		
<b>Motor current and voltage</b>		✓	✓					
<b>Minimum pick-up voltage</b>		✓	✓					
<b>Dynamic resistance</b>			✓			✓		
<b>First trip</b>			✓	✓				
<b>Under-voltage release</b>			✓				✓	
<b>Measurements</b>								
<b>Pass / Fail</b>			✓					✓
<b>Motion</b>	Analog	✓	✓					
	Digital	✓	✓					
	Absolute	✓	✓					
	Relative	✓	✓					
<b>Auxiliary contacts</b>	Timing	✓	✓					
	External trig	✓	✓					
<b>Coil currents</b>		✓	✓					
<b>Other functions</b>								
<b>Files and reporting</b>	PDF export	✓	✓					
	XML export		✓					
	Backup/restore breaker file	✓	✓					
	CABA Win compatible <sup>1</sup>	✓	✓	✓	✓	✓	✓	
	Templates	✓	✓					
	Printing	Activated if printer option available						
<b>Part number</b>		<b>CM-8010X</b>	<b>CM-8020X</b>	<b>CM-8006X</b>	<b>CM-8002X</b>	<b>CM-8003X</b>	<b>CM-8005X</b>	<b>CM-8007X</b>

<sup>1</sup> See the User Guide for details

## Circuit breaker testing accessories

Megger carries an uniquely complete assortment of various accessories, leads, transducers and mounting kits.

- For a complete list of accessories, see the circuit breaker accessory catalog. Use QR code to download



## ORDERING INFORMATION

Item	Part no
<b>EGIL221</b>	
2 brk/ph, 1 analog ch, no accessories	CM-22100
2 brk/ph, 1 analog ch, printer, no accessories	CM-22101
2 brk/ph, 1 analog ch, high voltage lead kit	CM-22190
2 brk/ph, 1 analog ch, printer, high voltage lead kit	CM-22191

<b>EGIL223</b>	
2 brk/ph, 3 analog ch, no accessories	CM-22300
2 brk/ph, 3 analog ch, printer, no accessories	CM-22301
2 brk/ph, 3 analog ch, high voltage lead kit	CM-22390
2 brk/ph, 3 analog ch, printer, high voltage lead kit	CM-22391

<b>EGIL241</b>	
4 brk/ph, 1 analog ch, no accessories	CM-24100
4 brk/ph, 1 analog ch, printer, no accessories	CM-24101
4 brk/ph, 1 analog ch, high voltage lead kit	CM-24190
4 brk/ph, 1 analog ch, printer, high voltage lead kit	CM-24191

<b>EGIL243</b>	
4 brk/ph, 3 analog ch, no accessories	CM-24300
4 brk/ph, 3 analog ch, printer, no accessories	CM-24301
4 brk/ph, 3 analog ch, high voltage lead kit	CM-24390
4 brk/ph, 3 analog ch, printer, high voltage lead kit	CM-24391

### Software package

Standard (included)	CM-8010X
Plus (includes all below)	CM-8020X

### Single feature add-ons

Online

- Includes VDS and First trip
- First trip test requires First trip kit, optional accessory
- HW requirement for VDS and CT-timing is EGIL21x
- HW requirement for First trip coil current analysis on three coils simultaneously is EGIL2x3

CM-8006X

DualGround™

- Requires DCM200, optional accessory
- Fits all EGIL200 models

CM-8002X

SDRM

- Requires SDRM201, optional accessory
- HW requirement for SRM/DRM on three contacts simultaneously is EGIL213.
- Minimum HW requirement for SRM/DRM on one contact at a time is EGIL211, EGIL223 or EGIL243

CM-8003X

Under-voltage release

CM-8005X

Pass / Fail

CM-8007X

### PC software

EGIL200 Viewer Expert	CM-8201X
-----------------------	----------

## ORDERING INFORMATION

Item	Part no
<b>EGIL211</b>	
1 brk/ph, 1 analog ch, no accessories	CM-21100
1 brk/ph, 1 analog ch, printer, no accessories	CM-21101
1 brk/ph, 1 analog ch, high voltage lead kit	CM-21180
1 brk/ph, 1 analog ch, printer, high voltage lead kit	CM-21181
1 brk/ph, 1 analog ch, medium voltage lead kit	CM-21190
1 brk/ph, 1 analog ch, printer, medium voltage lead kit	CM-21191
<b>EGIL213</b>	
1 brk/ph, 3 analog ch, no accessories	CM-21300
1 brk/ph, 3 analog ch, printer, no accessories	CM-21301
1 brk/ph, 3 analog ch, high voltage lead kit	CM-21380
1 brk/ph, 3 analog ch, printer, high voltage lead kit	CM-21381
1 brk/ph, 3 analog ch, medium voltage lead kit	CM-21390
1 brk/ph, 3 analog ch, printer, medium voltage lead kit	CM-21391

### Postal address

Megger Sweden AB  
Box 724  
SE-182 17 Danderyd  
SWEDEN

T +46 8 510 195 00  
E seinfo@megger.com

### EGIL200\_DS\_en\_V07

ZI-CM01E • Doc. CM036525HE • 2026  
Subject to change without notice  
Megger Sweden AB  
Registered to ISO 9001 and 14001  
The word 'Megger' is a registered trademark

www.megger.com

**Megger**<sup>®</sup>